



SC-05 ONLY-ONE VIDEO INTERCOM

**CUSTOMISE
THE SCREEN
with
YOUR LOGO**
see page X

- + **Integrated antenna** on the front panel for optimum GSM signal reception
- + **Surface mounted installation**
- + **Colour LCD display** with sensor for brightness adjustment
- + **Hands-free reader**
- + **12 keys backlit** coded keypad
- + **Integrated GSM module**



INSTALLATION MANUAL



www.intratone.info

SC-05 ONLY-ONE VIDEO INTERCOM RANGE

ONLY-ONE INTERCOM

Zamak finish

**1 INTERCOM
+ 1-DOOR CENTRAL UNIT**
// 20 black key fobs

06-0228

DESCRIPTION and TECHNICAL SPECIFICATIONS

INTERCOM

DIMENSIONS (W x H x D)	Only-One intercom	120 x 266 x 46 mm
ENVIRONMENT	Operating temperature	-20°C to +60°C
	Index protection	IP54 / IK08
ACCESS CONTROL EQUIPMENT	Coded keypad	✓
	Hands-free reader	✓
INSTALLATION	Outdoor / Indoor	✓
	Surface-mounted	✓
	Accessibility needs compliant	✓
	Hearing loop	✓
	Braille keypad	✓
	Time taken to connect	40 sec.
ADDITIONAL INFORMATION	Accelerated alphabetical searching	✓
	Name or flat number displayed on time slots	✓
	6.5 x 3.6 cm colour LCD screen	✓
	Functional messages: (call in progress, etc.) Voice synthesis + display	✓
	Anti-disturbance (I)	✓
	Sound level adjustment without dismantling	✓
	Automatic call return if no answer	✓

(I) System to prevent residents being disturbed by repeated calls

CENTRAL UNIT

CENTRAL UNIT CHARACTERISTICS	Power supply recommended (not included)	12 VDC 5A - 24 VDC 2,5A
SYSTEM	Number of relays	1 (+3)



1-door - 03-0102

SERVICE PACKAGE

PREPAID

Sirocco offer*
+
unlimited data synchronisation 15 years

**PREPAID
15 YEARS**

*4G-IP module included

SIMPLIFIED SCHEME and WIRING

